

**NORTON**



## Concrete & Asphalt ▶ **C99 Floor Saw**

The Clipper **C99** is a compact and economical floor saw, for wet or dry cutting of asphalt or concrete. The outstanding cutting performance is obtained by the optimal weight distribution. The positioning of the 20 litre water tank adds weight onto the blade while maintaining an excellent view of the cutting operation. By means of a handwheel the operator can adjust the

cutting depth, indicated by a gauge (patent pending). The handle is adjustable to the operator height and stays level at any cutting depth. Vibration is kept to a minimum with the heavy-duty frame of the C99 which will extend the machine life and add comfort to the operator. The best performance is obtained with genuine Norton dry or wet cutting diamond blade.

**clipper**

Concrete & Asphalt ▶ **C99 Floor Saw**

**Features**

- ▶ Continuous depth control with a hand-wheel. The depth is indicated by a gauge (patent pending).
- ▶ Easy to service 4 V belts drive.
- ▶ Cutting depth up to 140 mm.
- ▶ Removable 20 litre polyurethane water tank with large opening for filling, Inbuild coupling for external water supply.
- ▶ Easily adjustable handle to the size of the operator. The handle stays at the same level at any cutting depth.
- ▶ Vibration reduced by heavy duty frame.
- ▶ Optimal weight distribution results in outstanding cutting performance.
- ▶ Shaft locking device for easy blade removing. Pivoting blade guard, stays permanently on the machine.
- ▶ Standard 20 mm twin blade mounting.
- ▶ Lifting hook in the center of gravity of the floor saw.
- ▶ Easy access to the fuel tank.
- ▶ All necessary tools stored on the control panel.
- ▶ Rear wheels and blade shaft bearings equipped with grease nipples.
- ▶ Rear wheel in recess from the cut and permits to cut in parallel of an open trench.
- ▶ Parking brake for safety.
- ▶ Heavy duty pillow block bearings on 30mm blade shaft.



Ergonomic working condition



Easy blade mounting. Parking brake

**Specifications**

**Model**

Model C99 PI3H	Petrol Honda GX390	9,6 kW (13HP)
Model C99 PI3H CYCLONIC	Petrol Honda GX390	9,6 kW (13HP)
Model C99 PI3K	Petrol Kohler CH13T	9,6 kW (13HP)
Modell C99 D7	Diesel HATZ 1B30	5 kW (7HP)
Modell C99 E75.3	Electric	5,5 kW 400 V 3~

**Characteristics**

Max. blade	∅	400 mm
Max. depth of cut	∅400	140 mm
	∅350	115 mm
Bore		25,4 mm
Twin blade mounting		20 mm
Blade shaft speed		2850 min <sup>-1</sup>
V-Belts		4
Water capacity		20 L
Sound pressure (Honda)		88 dB(A)
Sound power (Honda)		105 dB(A)

**Dimensions / Weight**

Length (Working)		1160 mm
Length (Transport)		850 mm
Width		512 mm
Height		990 mm
Weight	Honda	99 kg
	Kohler	111 kg
	Hatz	107 kg
	Elektro	105 kg



Depth gauge, lifting hook.



Designed for use with Clipper wet or dry cutting diamond blades

[www.norton-diamond.com](http://www.norton-diamond.com)

**NORTON DIAMOND PRODUCTS**

Unit 2, Meridian West  
 Meridian Business Park  
 Leicester LE3 2WX, England  
[www.norton-diamond.com](http://www.norton-diamond.com)  
[nlesal@norton.saint-gobain.com](mailto:nlesal@norton.saint-gobain.com)

Tel.: +44 (0)116 263 23 02  
 Fax: +44 (0)116 282 72 92  
 Free Fax: 0800 62 23 85

Sold and supported by:

